

A Presentation onboard Golden Princess

Dr Wei Chen, Head of R&D
26th OCT 2009

Why trials?

- ▶ **Current AWP's can not meet the limits.**
- ▶ **There is a lack of evidence the requirements can be consistently met for shipboard applications.**
- ▶ **Unique shipboard conditions, such as**
 - ▶ **High Temperature**
 - ▶ **High concentrations**
 - ▶ **Fluctuations**
 - ▶ **Constraints on space and operational resource**
- ▶ **Technologies – well proven in land based applications only**
 - ▶ **N – biological nitrogen removal**
 - ▶ **P – chemical precipitation**

Nitrogen compounds

Terminologies

TN = Total Kjeldahl nitrogen (TKN) + Total oxidised nitrogen (TON)

TKN = Ammonia (NH-N) + organic nitrogen

NH-N = Ammonia (NH-N)

TON = nitrite-N + nitrate-N

In untreated wastewater, $TKN > NH-N$. TON is absent.

In treated wastewater, $TKN \approx NH-N$ due to hydrolysis of organic N. Present of TON is the result of nitrification.

Nitrification

- ▶ **Two-step reaction:**



Bacteria involved are generally termed Nitrifiers - slow growing and valnerable.

- ▶ **Oxygen requirement 4.6 kg/kg N oxidised**
- ▶ **Alkalinity requirement 7.14 kg as CaCO₃/kg N oxidised**
- ▶ **Nitrite will accumulate at inhibitive (e.g. low DO), high temperature, or transition conditions.**

Influential factors to nitrification

- ▶ **Longer sludge age > 8~15 days**
 - ▶ Nitrifiers grow slower and less
- ▶ **More aeration demand, DO >1.5~2 mg/l**
 - ▶ Nitrobacters are inhibited at low DO. (Double of carbon removal)
- ▶ **Alkalinity demand. Optimum pH 7.5~8.**
 - ▶ Nitrification tends to reduce pH. Nitrifiers are pH sensitive. Rate at pH6 is 10% of that at pH7.
- ▶ **Temperature is important, optimal 25 °C~35 °C**
 - ▶ Nitrifiers are temperature sensitive.
- ▶ **Toxic and inhibitory compounds**
 - ▶ Nitrifiers are very vulnerable to toxicity and a wide range of organic and inorganic compounds comparing to heterotrophs

Effect of Temperature - uncertainties





Fig 3.7 Nitrification as a function of temperature. As opposed to the other biological processes in wastewater treatment, thermophilic nitrifying bacteria are unknown.

Nitrification Design – Discharge limit

- ▶ Treatment standards
 - ▶ A lower NH-N limit requires nitrifiers to domain under a low NH-N environment, at a lower growth rate.

$$\mu_{\text{NH-N}} = \mu_{\text{NH-N, MAX}} \times [\text{NH-N}] / (K_N + [\text{NH-N}])$$



- ▶ Standards $\uparrow \rightarrow$ design F:M $\downarrow \rightarrow$ Biomass $\uparrow \rightarrow$ Reactor V \uparrow

Denitrification

- ▶ Anoxic condition - present of Nitrate with no **DO**.
- ▶ $\text{NO}_3^- + \text{C (or BOD)} \rightarrow \text{CO}_2 (\uparrow) + \text{N}_2 (\uparrow) + \text{OH}^-$ (by heterotrophs)
- ▶ Total BOD requirement 2.86 kg/kg N denitrified.
- ▶ Alkalinity producted 3.57 kg as CaCO_3 /kg N denitrified.
- ▶ Denitrification reduces the total power consumption.
- ▶ Denitrification assists to stabilise the alkalinity balance.

Conditions for Denitrification

- ▶ **DO** <0.3 mg/l.
 - ▶ DO inhibits denitrification.
 - ▶ To limit DO in the re-circulation
 - ▶ To avoid air entrapment in anoxic zone mixing etc.
 - ▶ To avoid cascading
- ▶ **Need readily degradable organic materials (good food).**
 - ▶ Govern the reaction rate, hence the size of anoxic tank.
- ▶ **Less sensitive to pH.**
- ▶ **Higher temperature benefits reaction rate?**

MBR for Nitrogen Removal on Ship






Diagram of N-DN process



Effluent NO-N and Recirculation R




P removal – chemical precipitation

- ▶ Iron and aluminium salts are used to precipitate the phosphorus from wastewater.
- ▶ P is removed with de-sludge.
- ▶ $\text{Fe}^{2+} + \text{O}_2 \rightarrow \text{Fe}^{3+}$
- ▶ $\text{Fe}^{3+} + \text{PO}_4^{2-} \rightarrow \text{Fe}_2(\text{PO}_4)_3 (\downarrow)$
- ▶ Typical ratio Fe:P = 2:1


Golden Princess Trial Plant - configurations

ALL COPYRIGHT AND DESIGN RIGHT SURVIVING IN THIS DOCUMENT IS THE PROPERTY OF HAMWORTHY WASTEWATER SYSTEMS LTD, AND MAY NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS, IN PART OR WHOLE, WITHOUT HAMWORTHY WASTEWATER SYSTEMS LTD CONSENT. THIS DOCUMENT AND THE INFORMATION WITHIN IT IS CONFIDENTIAL TO HAMWORTHY WASTEWATER SYSTEMS LTD, AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF HAMWORTHY WASTEWATER SYSTEMS LTD.




Golden Princess Trial Plant - configurations

ALL COPYRIGHT AND DESIGN RIGHT SURVIVING IN THIS DOCUMENT IS THE PROPERTY OF HAMWORTHY WASTEWATER SYSTEMS LTD, AND MAY NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS, IN PART OR WHOLE, WITHOUT HAMWORTHY WASTEWATER SYSTEMS LTD CONSENT. THIS DOCUMENT AND THE INFORMATION WITHIN IT IS CONFIDENTIAL TO HAMWORTHY WASTEWATER SYSTEMS LTD AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF HAMWORTHY WASTEWATER SYSTEMS LTD.



Golden Princess Trial Plant - configurations

ALL COPYRIGHT AND DESIGN RIGHT SURVIVING IN THIS DOCUMENT IS THE PROPERTY OF HAMWORTHY WASTEWATER SYSTEMS LTD, AND MAY NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS, IN PART OR WHOLE, WITHOUT HAMWORTHY WASTEWATER SYSTEMS LTD CONSENT. THIS DOCUMENT AND THE INFORMATION WITHIN IT IS CONFIDENTIAL TO HAMWORTHY WASTEWATER SYSTEMS LTD AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF HAMWORTHY WASTEWATER SYSTEMS LTD.




Program


- **Ship survey completed** **Nov 2008**
- **Scope of work and contract agreement** **Jan 2009**
- **Phase 1 (wastewater characterisations) completed** **Apr 2009**
- **Phase 2 (installation and commissioning) completed** **Jun 2009**
- **Phase 3 (trial period) started** **Jul 2009**
 - **Scenario 0 (setting up) completed** **Jul 2009**
 - **Scenario 1 completed** **Sep 2009**
 - **Scenario 2 completed** **Oct 2009**
 - **Scenario 3 (P removal) to be completed** **Nov 2009**
 - **Scenario 4/5** **Jan 2010**

Phase 1 Findings

Black Water Characteristics




Sanitary Grey Water Characteristics



Phase 1 Findings

MBR 3 Permeate



Phase 1 Findings


- ▶ **Black water ammonia has 600-1000 mgN/l comparing to 40-60 mgN/l in the municipal sewage.**
- ▶ **Grey water has very low ammonia concentrations. Grey water treatment in MBR (3~4:1) dilutes black water ammonia.**
- ▶ **Extreme fluctuation of wastewater and permeate characteristics.**
- ▶ **Partial nitrification occurs in MBR.**
- ▶ **High temperature.**
- ▶ **The on-line ammonia monitoring was proven.**
- ▶ **A set of MBR improvements identified.**

Phase 3 – Scenario 0-1

- ▶ Data log sheets and communication were established.
- ▶ A set of operational parameters.
 - ▶ MBR capacity reduced to 90-100 m³/day.
 - ▶ Stable sludge age maintained to 18-30 days.
 - ▶ ISF flows being regulated.
 - ▶ Anoxic zone started.
 - ▶ DO increased to >1.5 mg/l.
 - ▶ Target grey:black ratio of 2:1.
 - ▶ Tank 5 level increased to improve buffering.
 - ▶ Alkaline dosing.
- ▶ Nitrification established.


Scenario 0-1 Findings

Ammonia removal



Scenario 0-1 Findings

Fluctuations




Scenario 0-1 Findings

- ▶ **Grey and black water mixing ratio is difficult to control. High fluctuation of ammonia in feed water.**
- ▶ **Constraints to some operational parameters in Alaska.**
- ▶ **Nitrification happens, but the ammonia reduction is not sufficient for compliance. (Temperature, ammonia too high, fluctuation)**
- ▶ **Stable denitrification could not be established. High nitrite. (Carbon limiting, temperature, mixing).**


Scenario 2 Findings

Scenario 2 - Start up and Performances



Scenario 2 Findings

On-Line meters Data Download (4 days)



Scenario 2 Findings

- ▶ Quick start-up of nitrification process when seeded from other MBR
- ▶ Nitrification has not improved further, by
 - ▶ Lower treatment capacity
 - ▶ Higher DO
 - ▶ Longer sludge age
- ▶ Accumulation of nitrate and nitrate

Further trial scenarios

- ▶ **Challenges**
 - ▶ **Plant observations and diagnosis**
 - ▶ **Data interpretation**
 - ▶ **Process stability**
- ▶ **Further scenarios**
 - ▶ **To increase Grey:Black ratio to 3:1**
 - ▶ **To treat all black water in MBR No.3**

Impact of increasing grey water treatment

Waste streams	Ammonia in combined black and grey water (mgN/l)	BOD/Ammonia ratio of the combined wastewater	Treated water due to biomass growth/disposal (mgN/l)	Reduction (%)	
Blk+50% sanitary	150	3.8	122	19%	
Blk+100% sanitary	82	4.8	62	24%	
Blk+sanitary +laundry	68	5	51	25%	
Blk+sanitary +laundry+ galley	50	8	30	40%	
Blk+sanitary +laundry+ galley +pulper water	50	11	23	55%	