

Materials List

1. Two Compartment Septic Tank

Size: _____

2. Aggregate

Sewer Rock

Size: _____

Quantity: _____

Sand Filter

Quantity: _____

3. Pipe Materials

4" Building Sewer (length in feet)

Schedule 40 ABS ASTM F628

4" Disposal Sewer (length in feet)

Schedule 40 ABS ASTM F628

Schedule 40 PVC ASTM D1785/ASTM D2665

SDR 35 PVC ASTM3034

4" Drainfield (length in feet)

Schedule 40 PVC ASTM D1785/ASTM D2665

SDR 35 PVC ASTM3034

4" Cleanout/Standpipe (length in feet)

Schedule 40 ABS ASTM F628

Schedule 40 PVC ASTM D1785/ASTM D2665

SDR 35 PVC ASTM3034

4. Miscellaneous

Couplings Needed (Caulder, Fernco, or equivalent)

Filter Fabric (enter amounts)

Typar 3401

Mirafi 140N

Insulation (Dow Chemical, Styrofoam HI or equivalent)

Quantity: _____

5. Other Materials

(List any sealants or other materials needed)

General Material Specifications

Couplings

Caulder, Fernco, or equivalent

Insulation

Dow Chemical Co. Styrofoam HI (Blue Board) or equivalent, minimum 40 psi

Septic Tanks

Must meet plumbing code requirements and be watertight

Wood Septic Tanks

NOT ACCEPTABLE

Filter Fabric

Typar 3401, Mirafi 140N, or equivalent

Sewer Rock

Sizing (requirements)

3/4" to 1.5" fine graded for bed or shallow trench systems

3/4" to 3" coarse graded for all other type of systems (deep trench, pits, five-wides)